

LIFT TRUCKS

FBT / LI-ION

ELECTRIC POWER STEERING • Easy operation

- · High operating precision
- Height adjustable steering wheel

CONTROL LEVER UNIT

· Comfortable fit on both sides

2 USB PORTS

- For charging your phone or scanner.
- It closes with a cover against water and dust.

LI-ION BATTERY

ON MODELS WITH LI-ION

- Turbo charging
- Batteries charge in half an hour to two hours (depending on capacity) without memory effect
- Up to 40% power saving while charging
- Sealed casing and standard reliability
- Charge indicator directly on the case

TISEL POWER MAST

- Side shift function of the carriage
- Proporational load lifting

LED LIGHTS

Additional lighting for better visibility

THE LEGENDARY "JAPANESE" SEAT

- Cushioning for maximum comfort
- Folds back for access to the battery
- Side support and presence detector
- Anatomically shaped for reduced fatigue



Cast tubeless tire with puncture protection

Convenient and quick replacement to keep working

4_{YEARS}

Extended warranty with timely maintenance

2LEUELS

Quality control before sale

129k UNITS

Equipment sold in the World


Parameter	FBT 16	FBT 18	FBT 20
Maximum lifting height (mm)	6000	6000	6000
Maximum payload (kg)	1600	1800	2000
Parameters of the Li-ION battery (optional)	48V / 300Ah	48V / 300Ah	48V / 300Ah
Forks length (mm)	920	1070	1070
Total length (mm)	2845	3000	3130
Total width (mm)	1135	1135	1135
Working corridor (800x1200) longitudinally (mm)	3322	3327	3357



Increased steering angle of the twin rear wheels gives the loader maximum maneuverability.



2 times more efficient operation due to Battery with Li-ION technology.



Multifunctional customizable LED panel with hour meter for accurate monitoring of charge level and timely maintenance.



HIGH-PERFORMANCE MATERIAL HANDLING AND PROMPT SERVICE

53Service centers

worldwide

Production sites around the world

Models of material handling for any business needs

ORDER ONLY FROM AUTHORIZED DEALERS

+49 (833) 277-22-92 general@tiseltechnics.com tiseltechnics.com