

MORE OPPORTUNITIES WITH MIN INVESTMENT

LED CHARGE INDICATOR AND HOUR METER

Accurate charge level monitoring for timely maintenance

INCREASED RESISTANCE TO LOADING

Due to the frame construction

BACK-PEDAL BRAKE

Electromagnetic brake prevents the cart from rolling away from an inclined plane if the operator loses control

OPTIONAL ENTRY CASTERS

Protects the undercarriage from shocks and allows you to smoothly overcome uneven floors.

REINFORCED STIFFENERS

Eliminates the possibility of deformation of the forks in case of overloading or improper distribution of the load on the forks.

F9 TISEL CONTROL® FUNCTIONAL HANDLE

- Waterproof and shockproof
- Versatile for all hands
- Controls with vertical handle position to reduce working aisle (AST)

STABILIZATION SYSTEM

Extra casters for greater stability



4

YEARS

Extended warranty with timely maintenance

2

LEVELS

Quality control before sale

129

K UNITS

The world's sold equipment

Parameter	ETL 125
Maximum payload (kg)	2500
Parameters of Li-ION battery	24v / 240Ah
Fork length (mm)	1150
Overall length (mm)	1748
Total width (mm)	710
Working lane (800x1200) longitudinally (mm)	2255



Operator safety button for safe operation.
Charge indicator and ignition key in visible view of the operator.



2 times more efficient operation due to Battery with Li-ION technology.



High resistance to temperatures from -30 to +50.
Maintains charge during long idle time due to Sleep Mode (sleep mode)

TISEL

TECHNICS

HIGH-PERFORMANCE MATERIAL HANDLING AND PROMPT SERVICE

53

Service Centers worldwide

7

Production sites around the world

197

Models of material handling for any business needs

ORDER ONLY FROM AUTHORIZED DEALERS

+49 (833) 277-22-92

general@tiseltechnics.com

tiseltechnics.com