

HT

HTD

HTG

CONVENIENT CONTROL SYSTEM

- Chromed handle with anti-slip coating
- Rubber coated foot-operated lift arm
- Smooth control of platform lowering via handy lever on the handle

PATENTED LIFTING SYSTEM TISEL X-FORCE

- High pressure hydraulic cylinders
- Heavy duty double chrome plated piston rods
- Reinforced design with metal rollers for shear movement



ULTRASTRENGTH STEERING WHEELS

Mechanical parking brake on the rear wheel for locking on the sloped floor.



UP TO 1500 MM

Maximum lifting height



UP TO 1000 KG

Maximum payload

4 YEARS

Extended warranty with timely maintenance

2 LEVELS

Quality control before sale

129 K UNITS

The world's sold equipment

Parameter	HT 15-100	HTD 35-70	HTG 50-100
Maximum lifting capacity (kg)	150-1000	350-700	500-1000
Lifting height (mm)	720-990	1300-1500	915-1360
Height when folded (mm)	220-410	355-445	290-360
Overall length (mm)	910-1350	1140-1450	1935-2370
Total width (mm)	450-600	500-610	750-810

OTHER TYPES OF SCISSOR LIFT TABLES



HTZ SERIES

STAINLESS STEEL

Load capacity up to 450 kg. Lift height up to 1300 mm.

- ✓ In food production
- ✓ In chemical production
- ✓ In pharmaceutical production



HTE SERIES

WITH ELECTRIC LIFT

To work more efficiently

Load capacity up to 750 kg.
Lift height up to 1300 mm.

TISEL

TECHNICS

HIGH-PERFORMANCE MATERIAL HANDLING AND PROMPT SERVICE

53

Service Centers
worldwide

7

Production sites around
the world

197

Models of material
handling for any business
needs

ORDER ONLY FROM AUTHORIZED DEALERS

+49 (833) 277-22-92

general@tiseltechnics.com

tiseltechnics.com