

SCISSOR LIFT TABLES



PATENTED LIFTING SYSTEM

TISEL X-FORCE

- High pressure hydraulic cylinders
- Heavy duty double chrome plated piston rods
- Reinforced design with metal rollers for shear movement

MODERN SECURITY SYSTEMS

An aluminum safety frame around the perimeter of the platform with microswitches will stop the lift table operation if any pressure is applied to it.

- Overload protection system
- IP54 dust and splash protection for outdoor use



- Dust and splash protection complies with IP54 (for outdoor use)
- Emergency quick disconnect button



TISEL

COMPLIES WITH EUROPEAN QUALITY AND SAFETY STANDARDS

En1570:1999EN1175-1



LP TO 1600 MM Maximum lifting height



UP TO 3000 KG Maximum payload



Extended warranty with timely maintenance



Quality control before sale



The world's sold equipment

Parameter	TLA 2000	TLB 2000-3000	TLX 500-3000
Maximum load capacity (kg)	2000	2000-3000	500-3000
Lifting height (mm)	1550	1850-1900	990-1200
Height when folded (mm)	250	250-300	190-250
Engine power (kW)	1,5	1,5	0,75-1,5
Power type, volts (V/Hz)	3x-380/50	3x-380/50	3x-380/50

OTHER TYPES OF LIFTING TABLES

Requiring no complicated installation or additional training





HIGH-PERFORMANCE MATERIAL HANDLING AND PROMPT SERVICE



Service Centers worldwide

Production sites around the world



Models of material handling for any business needs

ORDER ONLY FROM AUTHORIZED DEALERS

+49 (833) 277-22-92

general@tiseltechnics.com tiseltechnics.com